



Care and Cleaning Instructions for Awnings

Fabric should be cleaned regularly before substances such as dirt, roof particles, etc. are allowed to accumulate on and become embedded in the fabric. The fabric can be cleaned without being removed from the installation. Simply brush off any loose dirt, roof particles, etc.; hose down and clean with a mild solution of natural soap in lukewarm water (no more than 100° F). Rinse thoroughly to remove soap. DO NOT USE DETERGENTS. Allow to air dry.

For more stubborn cases: Soak the fabric for approximately twenty minutes in a solution of no more than ½ cup (4oz.) of a non-chlorine bleach and ¼ (2oz) natural soap per gallon of water at approximately 100° F. Rinse thoroughly in cold water to remove all of the soap. Note: Excessive soaking in non-chlorine bleach can deteriorate sewing threads. This method of cleaning may remove part of the water repellency and the fabric should receive and application of an air curing fluorocarbon water repellent treatment, such as 303 Hi Tech Fabric Guard, if water repellency is a factor.

Awning Fabric is made from 100% solution dyed acrylic fiber which is thermoplastic. DO NOT SUBJECT TO EXCESSIVE HEAT. When fabric is stored, it should be cleaned, allowed to air dry and stored in a dry, well ventilated area.

*For more information please contact your
Inside Outfitters Sales Representative.*